




## MOTIP Kompakt Car Paint

Ord.-no.: look at ordering information

## Technical Information



MOTIP Car Paint is a high quality, fast-drying lacquer for the repair of car parts, based on the original car colours. Car paint is very suitable for repairing scratches, stone chip damage and small dents.

### Quality & properties

- Original car colour
- Fast drying
- Excellent coverage and filling property
- Lasting colour and gloss
- Scratch free and shock proof
- Resistant to weather influences
- UV resistant and non-fading
- Corrosion preventive
- Excellent adhesion

### Physical & chemical data

- Base: Acrylic resin
- Colourname:
  - Red
  - Brown
  - Orange
  - Yellow
  - Green
  - Blue
  - Purple
  - White
  - Beige
  - Grey
  - Black
  - Anthracite metallic
  - Red pearl
  - Gold
  - gold
  - Yellowish green
  - Silver
  - Blue purple
  - blue
  - Blue
  - White
  - red
  - black
  - grey
  - brown
  - silver
  - white
  - beige
  - bronze
- Degree of gloss: gloss, >75 GU
- Dry to touch: 20 min
- Completely dry: 2 h
- Overcoatable: 2 h
- Surfaces: Car parts
- Vapour pressure: 8300/20 bar
- Flash point: n.a. °C
- Storage stability: 10 years
- Content: 400 ML

### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface
- Apply a layer of MoTip primer suitable for the surface. After drying, sand the base layer (grain 600).
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C.
- Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.
- Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.

- For an optimum result, apply a finishing layer of acrylic clear varnish.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

**Environmentally sound**

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal**

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labeling**

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

**As of December 3, 2021** – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)  
European Aerosols B.V., Wolframweg 2, NL-8471 XC Wolvega - [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)